


Model 5060 Thermoelectric Generators



Global Thermoelectric's Model 5060 Thermoelectric Generator contains no moving parts. It is a reliable, low maintenance source of DC electrical power for any application where regular utilities are unavailable or unreliable.

Power Specifications

Power Rating at 20°C

60 Watts at 6.7 Volts

54 Watts at 12 Volts

54 Watts at 24 Volts

54 Watts at 48 Volts

Electrical

Adjustment:	6.7V	up to 11 Volts
	12 V	12 - 18 Volts
	24 V	24 - 30 Volts
	48 V	48 - 60 Volts

Reverse current protection included.

Output: Terminal block which accepts up to 8 AWG wire. Opening for 3/4" conduit in the base of the cabinet.

Standard Features

- Automatic Spark Ignition (SI)
- Automatic Fuel Shut-off (SO)
- Fuel Filter
- Low Voltage Alarm Contacts (VSR)
- Volt & Amp Meter

Optional Features

- Cathodic Protection Interface
- Pole Mount or bench stand
- Corrosive Environmental Fuel System
- Flame Arrestor

Note: Specifications shown are for standard configurations. Global Thermoelectric's Integrated Systems Engineering Department is available to design custom voltages, fuel supply systems and non-standard operating temperatures.

Fuel

Natural Gas:	4.4 m ³ /day (155 Sft ³ /day) 1000 BTU/Sft ³ (37.7 MJ/SM ³) gas max 7 mg/Sm ³ (~5 ppm) H ₂ S max 120 mg/Sm ³ H ₂ O max 1% free O ₂
Propane:	5.7 l/day (1.5 US gal/day)
Max. Supply Pressure:	1724 kPa (250 psi)
Min. Supply Pressure:	103 kPa (15 psi)
Fuel Connection:	1/4" MNPT

Environmental

Ambient Operation Temperature: Max. 45°C (115°F) Min. -40°C (-40°F).

Operating Conditions: Unsheltered operation


Please contact Global for operating conditions below -40°C or above +45°C.

Materials of Construction


Cabinet:	304 SS
Cooling Type:	Natural Convection
Fuel System:	Brass, Aluminum & SS



Typical Installation



- NOTES:
1. GENERATOR WEIGHT: 41 kg [100 lb]
 2. DIMENSIONS IN mm [INCHES].



Power where you need it.

Corporate Office
 9, 3700 - 78 Avenue SE
 Calgary, Alberta T2C 2L8 CANADA
 Phone: (403) 236-5556
 Fax: (403) 236-5575
 www.globalte.com

US Sales
 P.O. Box 38624
 Houston, TX 77238
 Phone: (281) 445-1515
 Fax: (281) 445-6060
 Toll Free: 1 800 848-4113

Model 5060 Thermoelectric Generator